6SF7

DIODE – SUPER-CONTROL AMPLIFIER PENTODE

SINGLE-ENDED METAL TYPE

Heater ■	Coated Unipotential Cathode	
Voltage	6.3	a-c or d-c volts
Current	0.3	amp.
Direct Interelectrode Capacitances: o		
Pentode Unit		
Grid to Plate	0.004 max.	μμf
Input	5.5	μμf
Output	6.0	μμf
Pentode Grid to Diode	0.002 max.	μμf
Pentode Plate to Diode	0.8	μμf
Maximum Overall Length		2-5/8"
Maximum Seated Height		2-1/16"
Maximum Diameter		1-5/16"
Bulb		Metal Shell, MT-8
Base		Small Wafer Octal 8-Pin
Pin 1 – Shell		Pin 5 – Diode Plate
Pin 2 – Pentode Grid		Pin 6 – Pentode Plate
Pin 3 – Cathode		Pin 7 – Heater
Pin 4 – Screen		Pin 8 – Heater
Mounting Position		Any



BOTTOM VIEW (7AZ)

PENTODE UNIT – AMPLIFIER

Plate Voltage		300 max.	volts
Screen Voltage		100 max.	volts
Screen-Supply Voltage		300 max.	volts
Grid Voltage		0 min.	volts
Plate Dissipation		3.5 max.	watts
Screen Dissipation		0.5 max.	watt
Typical Operation and Characteristics – Class A_1 Amplifier:			
Plate	100	250	volts
Screen	100	100	volts
Grid	-1	-1	volts
Plate Resistance (Approx.)	0.2	0.7	megohm
Transconductance	1975	2050	μmhos
Grid Bias (Approx.) †	-35	-35	volts
Plate Current	12	12.4	ma.
Screen Current	3.4	3.3	ma.

DIODE UNIT – One

Consideration of this unit is similar to that given under Type 6B8-G with the exception that there is one diode in Type 6SF7. Diode curves shown under Type 6B7 apply to the 6SF7.

■ In circuits where the cathode is not directly connected to the heater, the potential difference between heater and cathode should be kept as low as possible.
o With shell connected to cathode.
† For transconductance of 10 μmhos.

← Indicates a change.

RCA RADIOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

6SF7

6SF7

AVERAGE PLATE CHARACTERISTICS

PENTODE UNIT



FEB. 20, 1941

RCA RADIOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

92C-6254